

## WATERPROOFING

# HIR CRACK LOCK

CRACK LOCK is an acrylic polymer based white crack filler paste made of acrylic emulsion polymer. It provides a strong bond with flexibility which accommodates the cracks in the plaster and provides a water resistant surface with aesthetic appearance.

### FEATURES

- Ready to use single component Paste.
- Excellent adhesion
- Improves flexural, tensile Strength
- Allows breathing, thus preventing peeling and scaling
- Non toxic
- UV resistant
- Better Elongation
- Paintable Products.
- Easy to apply by putty knife similar to conventional putties.

### APPLICATION

- For Internal crack repairs
- For external crack repairs from Hair line to 3 mm in width
- For hair line cracks in painted surfaces that result in internal water leakage



### SURFACE PREPARATION

**Before Application of grout, Epoxy Grout, Tile Adhesive, Waterproofing. Crack and Sealant**

- All concrete and steel surfaces must be clean, dry and free from any contaminants such as all loose concrete, dust, oil, wax, grease, curing component or other substances that may affect adhesion performance, must be thoroughly cleaned with the help of wire brush, vacuum cleaner, scrubber. Remove excess and standing water with cloth and sponge.
- Use of HIR SBR bond is necessary to provide better strength to the concrete repair material.
- Make sure the surface is not too smooth, roughing any surface because the rough surface gives a firm grip.

**Pack:** 1Kg  
**Coverage\*:** NA  
**Color:** White and paintable