



**HIR**<sup>®</sup>  
YOUR BUILDING MASTER



AMERICAN  
TECHNOLOGY



GERMAN  
TECHNOLOGY

## TECHNICAL DATA



# HIR SALT X WATERPROOFING



Aesthetic  
Look



UV  
Resistant



Strength



Waterproofing



Anti Crack



Self Curing



No Air  
Bubble



Bonding



Breathable



Light Weight

## DESCRIPTION

HIR SALT X is high quality modified Acrylic Polymer base Water Repellent waterproofing master.

## FEATURES

- HIR SALT X is like Umbrella for home.
- Flexible and covers hairline cracks (up to 0.5 mm) effectively so that no ingress of water.
- Corrosion resistance
- Dirt pick up resistance
- Low VOC
- It is ready to use. No Dilution required.
- UV resistant – Resistance to UV
- Ease of application – User friendly, easily applicable by brush, roller or spray.

## AREA APPLICATION

- All types of exterior masonry surfaces, concrete, cement sand renderings, etc.
- Applicable on asbestos sheets.

Coverage: 400 Sq.ft/10ltr/100microns/2Coats\*  
Pack: 10Ltr

## APPLICATION OF HIR SALT X

- Surface should be perfectly cured, dry and hard.

### SURFACE PREPARATION

- a) The surface for waterproofing application has to be clean with wire brush as that all loose particles and dust can be removed.
- b) Use Blower or Vacuum cleaner to remove fine dust.

## APPLICATION

- Use HIR SALT X directly from the container. Stir contents well before use.
- Apply two neat coats of HIR SALT X with dilution with water in ratio 1:1 by brush or roller at a time interval of 5-6 hours.
- For enhanced protection, apply additional coat of HIR SALT X on rain lashing walls, chajjas and parapet walls.
- Allow the coated surface to air cure fully for 7 days

## Packing :1Ltr

## TECHNICAL DATA

COLOUR IN BUCKET	Milky white
COLOUR AFTER APPLICATION	Clear after drying
TOUCH DRY TIME	5 to 10 minutes
CRACK BRIDGING	0.5mm
DENSITY	1.04
PH VALUE	8.0 to 9.0
SELF LIFE	12 months

## NOTE :

- SURFACE TO BE APPLIED SHOULD BE MINIMUM 6 TO 8 WEEKS AGED (OLD).
- Shake well before use.
- Do not add other additive can effect the final result.
- Do not apply during rains or in direct sunlight.
- Do not tint the primer
- Keep the container tightly closed to prevent drying.
- Keep out of reach of children.

## Safety and Precaution

- Always wear safety gear while handling of any chemical products.
- Wash skin with soap & water after coming in contact with skin.
- Immediately splash eyes with plenty of water. Consult Physician if irritation persists.